

## Use and maintenance of round slings EN 1492-2

You receive this user manual with the delivery of the round slings.

### Before each use:

Visual inspection for damage

Label: Proof of the lifting capacity for each use

The round-sling is made of polyester PES and is not appropriate for the use in the area of alkaline/ bases. If the round-sling contaminated with bases, the round-sling has to be immediately rinsed with water and must be competently inspected.

Operating temperature: - 40 degree Celsius + 100 degree Celsius

### After each use:

Visual inspection for damage

Do not expose the round-slugs to the direct sunlight between each use.

Storage temperature: - 40 degree Celsius + 100 degree Celsius

### In case of damage:

Made round-sling unusable and dispose it to the waste

### General Notice:

- Note the lifting capacity and use. Information on the label.
- Note the effective working length (EWL)
- For several connecting/ mounting points use every time the same type of round-sling
- Work only with proven mounting technics
- If you have several mounting points only two or three round-slugs carry the weight. Consider the lifting capacity.
- Do not use the round-sling on sharp edges or use additional protection
- Safe the load for toss back, the center of gravity must be under the connection/ mountain point
- If you use round-sling parallel use spacers in order to avoid the round-slugs slip together
- If you wrap the load the aim is that you use an angle of 120° by double wrapping
- When lifting necessarily leave the hazardous area
- Arrange a lifting test
- Clear instructions, especially if you lift the load
- Occurs problems during the lifting test, the load must be settled down, checked and re-positioned